

SULIT



**BAHAGIAN PEPERIKSAAN DAN PENILAIAN
JABATAN PENDIDIKAN POLITEKNIK
KEMENTERIAN PENDIDIKAN TINGGI**

JABATAN KEJURUTERAAN MEKANIKAL

PEPERIKSAAN AKHIR

SESI JUN 2017

DJJ2073 : THERMODYNAMICS

TARIKH : 31 OKTOBER 2017

MASA : 2.30 PETANG - 4.30 PETANG (2 JAM)

Kertas ini mengandungi **SEMBILAN (9)** halaman bercetak.

Struktur (4 soalan)

Dokumen sokongan yang disertakan : Formula dan jadual stim

JANGAN BUKA KERTAS SOALAN INI SEHINGGA DIARAHKAN

(CLO yang tertera hanya sebagai rujukan)

SULIT

INSTRUCTION:

This section consists of **FOUR (4)** questions. Answer **ALL** questions.

ARAHAN:

Bahagian ini mengandungi EMPAT (4) soalan. Jawab SEMUA soalan.

QUESTION 1**SOALAN 1**

CLO1
C1

(a) Define:

Takrifkan:

i. Properties

Sifat

[2 marks]
[2 markah]

ii. Intensive properties

Sifat intensif

[2 marks]
[2 markah]

iii. Extensive properties

Sifat ekstensif.

[2 marks]
[2 markah]

CLO1
C2

(b) Convert each of the following units:

Tukarkan setiap unit-unit berikut:

i. 8.64 km/h to m/s

[2 marks]

8.64 km/j kepada m/s

[2 markah]

ii. 1200 kg/m³ to g/cm³

[3 marks]

1200 kg/m³ kepada g/cm³

[3 markah]

iii. 25 Watt to kJ/hr

[3 marks]

25 Watt kepada kJ/jam

[3 markah]

CLO1
C2

- (c) A mass of 0.23 kg gas is at a temperature of 20 °C, pressure 135 kN/m² and volume 0.22 m³. If the gas has a value of $C_v = 720 \text{ J/kgK}$, determine:

Sejumlah gas berjisim 0.23 kg mempunyai suhu 20 °C, tekanan 135 kN/m² dan berisipadu 0.22 m³. Jika gas tersebut mempunyai nilai $C_v = 720 \text{ J/kgK}$, tentukan:

- i. Gas constant (R)

Pemalar gas (R)

[5 marks]
[5 markah]

- ii. Gas molecular weight (M)

Berat molekul gas (M)

[2 marks]
[2 markah]

- iii. Specific heat at constant pressure (C_p)

Pekali haba tentu pada keadaan tekanan malar (C_p)

[2 marks]
[2 markah]

- iv. Specific heat ratio (γ)

Nisbah haba tentu (γ)

[2 marks]
[2 markah]

QUESTION 2

SOALAN 2

- CLO1
C1 (a) Give **THREE (3)** characteristics of an adiabatic process.
*Berikan **TIGA (3)** ciri-ciri proses adiabatik.*

[6 marks]
[6 markah]

- CLO1
C2 (b) A quantity of air occupied a pressure of 1.2 bar, volume of 0.334 m^3 and temperature of 29°C . Then the air is compressed at constant pressure until the volume becomes 0.18 m^3 . Calculate the mass and the final temperature for the air.

Suatu kuantiti udara berada pada tekanan 1.2 bar, isipadu 0.334 m^3 dan suhu 29°C . Udara tersebut kemudiannya dimampatkan pada tekanan malar sehingga isipadu akhir 0.18 m^3 . Kirakan jisim dan suhu akhir udara tersebut.

[6 marks]
[6 markah]

SULIT

CLO1
C3

- (c) Nitrogen (molar mass 28 kg/kmol) expands reversibly in a perfectly thermally insulated cylinder from 3.5 bar, 200°C to a volume of 0.09 m³. If the initial volume occupied was 0.03 m³ and the nitrogen is assumed as a perfect gas with $C_v = 0.741$ kJ/kg.K, calculate:

Nitrogen (jisim molar 28 kg/kmol) mengembang secara boleh balik di dalam silinder yang ditebat daripada 3.5 bar, 200 °C kepada isipadu 0.09 m³. Jika isipadu awal nitrogen adalah 0.03 m³ dan nitrogen dianggap sebagai gas sempurna dengan $C_v = 0.741$ kJ / kg.K, kirakan:

- i. The gas constant

Pemalar gas

[4 marks]
[4 markah]

- ii. The final gas pressure

Tekanan akhir gas

[6 marks]
[6 markah]

- iii. The work input

Kerja masukan gas

[3 marks]
[3 markah]

SULIT

QUESTION 3

SOALAN 3

CLO1
C1

- (a) State **THREE (3)** conditions which must be satisfied by the fluid during the steady flow energy analysis.

*Nyatakan **TIGA (3)** keadaan yang mesti dipenuhi oleh bendalir semasa analisis tenaga aliran mantap.*

[6 marks]
[6 markah]

CLO1
C2

- (b) The Steady Flow Energy Equation may be applied to any apparatus. With a sketch, explain the application of the steady flow energy in :

Persamaan Tenaga Aliran Mantap boleh digunakan untuk semua jenis perkakas. Dengan lakaran, terangkan penggunaan tenaga aliran mantap dalam :

- i. The boiler
Dandang

[3 marks]
[3 markah]

- ii. The condenser
Pemeluwap

[3 marks]
[3 markah]

CLO1
C3

Fluid with a specific enthalpy of 4100 kJ/kg enters a horizontal nozzle with negligible velocity at the rate of 79200 kg/h. At the outlet, the specific enthalpy and specific volume of the fluid were 3050 kJ/kg and 1.45 m³/kg respectively. Assuming the flow is an adiabatic flow process, find the:

Bendalir dengan entalpi tentu 4100 kJ/kg memasuki sebuah muncung mendatar dengan halaju yang boleh diabaikan pada kadar 79200 kg/h. Pada bahagian keluaran, entalpi tentu dan isipadu tentu bendalir adalah 3050 kJ/kg dan 1.45 m³/kg. Andaikan aliran adalah proses adiabatik, tentukan:

i. Velocity outlet

Halaju keluar

[7 marks]

[7 markah]

ii. Required outlet area of the nozzle

Luas bahagian keluar muncung

[6 marks]

[6 markah]

SULIT

QUESTION 4
SOALAN 4

CLO1
C1

(a) Define the following terms:

Takrifkan istilah-istilah berikut:

i. Second Law of Thermodynamics

[2 marks]

Hukum Kedua Termodinamik

[2 markah]

ii. Heat Engine

[2 marks]

Enjin Haba

[2 markah]

iii. Thermal efficiency

[2 marks]

Kecekapan terma / haba

[2 markah]

CLO1
C2

(b) Heat is transferred to a heat engine from a furnace at a rate of 255 GJ/hr. If the rate of waste heat rejection to a nearby river is 168 GJ/hr, determine the net work done and the thermal efficiency for this heat engine.

Haba dipindahkan ke enjin haba daripada relau pada kadar 255 GJ/jam. Jika kadar pembuangan haba ke sungai yang berhampiran adalah 168 GJ/jam, tentukan kerja bersih yang dilakukan dan kecekapan haba untuk enjin haba ini.

[9 marks]

[9 markah]

CLO1
C3

- (c) A steam power plant operates between a boiler pressure of 40 bar and a condenser pressure of 0.04 bar. If steam enters to the turbine at dry saturated state. For a Rankine cycle, determine:

Sebuah penjana kuasa steam bekerja di antara tekanan dandang 40 bar dan tekanan pemeluwap 0.04 bar. Sekiranya stim masuk ke dalam turbin pada keadaan tepu kering, tentukan untuk kitar Rankine:

- (i) The feed pump work.

Kerja pam suapan.

[2 marks]

[2 markah]

- (ii) The Rankine efficiency.

Kecekapan kitar Rankine.

[6 marks]

[6 markah]

- (iii) The specific steam consumption.

Penggunaan stim tepu.

[2 marks]

[2 markah]

SOALAN TAMAT

1. PROPERTIES OF PURE SUBSTANCE

Steam

$$v = xv_g \quad h = h_f + xh_{fg} \quad u = u_f + x(u_g - u_f) \quad s = s_f + xs_{fg}$$

Ideal Gas

$$PV = mRT \quad R = \frac{R_o}{M} \quad R = C_p - C_v \quad \gamma = \frac{C_p}{C_v}$$

2. FIRST LAW OF THERMODYNAMICS

$$\Sigma Q = \Sigma W \quad Q - W = U_2 - U_1$$

Flow Process

$$\dot{m} = \rho CA (\text{kg/s}) = \frac{CA}{V} \quad h = u + pv = C_p \Delta T$$

$$Q - W = \dot{m} \left[(h_2 - h_1) + \left(\frac{C_2^2 - C_1^2}{2} \right) + (Z_2 - Z_1)g \right]$$

Non-Flow Process

1. Isothermal Process ($PV = C$)

$$U_2 - U_1 = 0 \quad Q = W$$

$$W = P_1 V_1 \ln \left(\frac{V_2}{V_1} \right) \quad @ \quad W = P_1 V_1 \ln \left(\frac{P_1}{P_2} \right)$$

$$Q = P_1 V_1 \ln \left(\frac{V_2}{V_1} \right) \quad @ \quad Q = P_1 V_1 \ln \left(\frac{P_1}{P_2} \right)$$

2. Adiabatic Process ($PV^\gamma = C$)

$$U_2 - U_1 = mC_v(T_2 - T_1) \quad W = \frac{P_1 V_1 - P_2 V_2}{\gamma - 1} = \frac{mR(T_1 - T_2)}{\gamma - 1}$$

$$Q = 0 \quad \frac{T_2}{T_1} = \left(\frac{P_2}{P_1} \right)^{\frac{\gamma-1}{\gamma}} = \left(\frac{V_1}{V_2} \right)^{\gamma-1}$$

3. Poltropic Process ($PV^n = C$)

$$U_2 - U_1 = mC_v(T_2 - T_1) \quad W = \frac{P_1V_1 - P_2V_2}{n-1} = \frac{mR(T_1 - T_2)}{n-1}$$

$$Q = \frac{\gamma - n}{\gamma - 1} \times W \quad \frac{T_2}{T_1} = \left(\frac{P_2}{P_1}\right)^{\frac{n-1}{n}} = \left(\frac{V_1}{V_2}\right)^{n-1}$$

4. Isobaric Process

$$U_2 - U_1 = mC_v(T_2 - T_1)$$

$$W = P(V_2 - V_1) = mR(T_2 - T_1)$$

$$Q = mC_p(T_2 - T_1)$$

5. Isometric Process

$$U_2 - U_1 = mC_v(T_2 - T_1)$$

$$W = 0$$

$$Q = U_2 - U_1 = mC_v(T_2 - T_1)$$

3. SECOND LAW OF THERMODYNAMICS

Heat Engine

$$\eta_{th} = \frac{W_{net,out}}{Q_H} = 1 - \frac{Q_L}{Q_H}$$

Refrigerator

$$COP_{R,rev} = \frac{T_L}{T_H - T_L} = \frac{1}{T_H/T_L - 1}$$

Heat Pump

$$COP_{HP,rev} = \frac{T_H}{T_H - T_L} = \frac{1}{1 - T_L/T_H}$$

Power Cycle

$$\eta_{Rankine} = \frac{(h_1 - h_2) - (h_4 - h_3)}{(h_1 - h_4)}$$

$$\text{Work Ratio} = \frac{(h_1 - h_2) - (h_4 - h_3)}{(h_1 - h_2)}$$

$$s.s.c = \frac{3600}{(h_1 - h_2) - (h_4 - h_3)}$$